

Cenio mounted cultivator		Cenio 3000 Special/Super	Cenio 3500 Special/Super	Cenio 4000 Special/Super
Working width (m)		3.00	3.50	4.00
Execution		rigid		
Transport width (m)		3.00	3.50	4.00
Transport length with road lights (m)		3.60		
Weight (kg) (Base machine, simplest execution)	Special	1,325	1,445	1,615
	Super	1,515	1,675	1,910
Linkage		3-point linkage mounted (Cat. 3/3N)		
No. of tines		10	12	13
Tine execution	Special	C-Mix Special tines with shear bolt overload safety protection		
	Super	C-Mix Super tines with pressure spring overload safety protection		
Number of tine rows		3		
Tine spacing in the row (cm)		90		92.4
Row spacing: tine section (cm)		30		30.8
Frame height (cm)		75		
Working depth: tine section (cm)		5–25		
Operational speed (km/h)		8–15		
Power requirement from (kW/HP)		75/105	90/125	105/140
No. of d/a tractor spool valves		0/1		

Illustrations, content and technical data are not binding! Deviations of technical data are possible depending on the equipment. The illustrations may deviate from the requirements for local road traffic regulations.

AMAZONEN-WERKE H. DREYER SE & Co. KG
P. O. Box 51 · 49202 Hasbergen-Gaste/Germany
Phone +49 (0)5405 501-0 · Fax +49 (0)5405 501-193

MI8389 (en_II) 05.21 Printed in Germany www.amazone.net E-Mail: amazone@amazone.net