Technical data:

ZA-M	1002 Special	1202	1502
Working width (m)		10 – 36	
Hopper capacity (l)	1,200	1,200	1,500
– with hopper extension 1 x S 500 (l)	1,700	1,700	2,000
– with hopper extension 2 x S 500 (l)	–	2,200	2,500
– with hopper extension 3 x S 500 (l)	–	2,700	3,000
– with hopper extension 1 x L 1000 (l)	–	2,200	2,500
– with hopper extension S 500 + L 1000 (l)	–	2,700	3,000
Payload (kg)	1,800	3,100	3,100
Fill height (m)	1.07	1.07	1.14
– with hopper extension 1 x S 500 (m)	1.21	1.21	1.28
– with hopper extension 2 x S 500 (m)	–	1.35	1.42
– with hopper extension 3 x S 500 (m)	–	1.49	1.56
– with hopper extension 1 x L 1000 (m)	–	1.35	1.42
– with hopper extension S 500 + L 1000 (m)	–	1.49	1.56
Filling width (m)	2.15	2.15	2.15
– with hopper extension 1 x S 500 (m)	2.16	2.16	2.16
– with hopper extension 1 x L 1000 (m)	–	2.76	2.76
Overall width (m)	2.44	2.44	2.44
– with hopper extension 1 x L 1000 (m)	–	2.93	2.93
Overall length (m)	1.42	1.42	1.42
Spreading disc speed (rpm)		720 (Standard speed)	
Weight of the base machine (kg) (Extensions S 500 + 27 kg / L 1000 + +60 kg)	309	319	332

Illustrations, content and technical data are not binding and may differ depending on the level of equipment. Country-specific road traffic regulations apply and must be complied with, meaning that special approval may be required. The permissible axle loads and total weights of the tractor should be checked. Not all the listed combination options are possible with all tractor manufacturers.

Ahead in the field and safe on the road: ZA-M

ZA – the spreader

AMAZONEN-WERKE H. DREYER SE & Co. KG
P. O. Box 51 · 49202 Hasbergen-Gaste/Germany
Phone +49 (0)5405 501-0 · Fax +49 (0)5405 501-193

MI9001 (en_II) 10.22 Printed in Germany www.amazone.net E-Mail: amazone@amazone.net