Technical data

ZA-V mounted spreaders

		ZA-V 1400	ZA-V 1700	ZA-V 2000	ZA-V 2200	ZA-V 2600	ZA-V 2700	ZA-V 3200	ZA-V 4200
Working width (m)		10 – 36							
Hopper capacity (l)		1,400	1,700	2,000	2,200	2,600	2,700	3,200	4,200
– with bolt-on extension S 600 (l)		2,000	2,300	2,600	–	–	–	–	–
– with bolt-on extension L 800 (l)		–	–	–	3,000	–	3,500	4,000	–
Payload (kg)	with Special frame	2,200	2,200	2,200	–	–	–	–	–
	with Super frame	3,200	3,200	3,200	3,200	3,200	3,200	3,200	–
	with Ultra frame	–	–	–	4,500	–	4,500	4,500	4,500
Filling height (m)		1.13	1.23	1.32	1.31	1.48	1.42	1.54	1.77
Filling width (m)		2.22	2.22	2.22	2.71	2.22	2.71	2.71	2.71
Total width (m)		2.55	2.55	2.55	2.92	2.55	2.92	2.92	2.92
Total length (m)		1.68	1.68	1.68	1.68	1.68	1.68	1.68	1.68
Drive		mechanical / hydraulic (ZA-V Profis Hydro)							
Min. weight (kg) (with PTO shaft, V-Set 2)		351	357	366	444	420	463	481	579

Illustrations, content and technical data are not binding! Technical data may deviate according to the level of equipment.
Machine illustrations can vary due to country-specific traffic legislation.





Ahead in the field and safe on the road: ZA-V

ZA – The spreader

AMAZONEN-WERKE H. DREYER SE & Co. KG
P. O. Box 51 · 49202 Hasbergen-Gaste/Germany
Phone +49 (0)5405 501-0 · Fax +49 (0)5405 501-193

MI7781 (en_II) 11.21 Printed in Germany www.amazone.net E-Mail: amazone@amazone.net